

The 13th AIM Workshop

### Low carbon scenarios in 2050, korea

-- An Application of Energy Snapshot Tool --

Feb. 16-18, 2008 NIES, Tsukuba, Japan

Chan PARK, Seoul National University Dong Kun LEE, Seoul National University Tae Yong JUNG, Asian Development Bank

# **Table of Contents**



Socio-economic projection

Model application and result







- Korea government recently organize T/F team to deal with climate change for the new economical policy (Korea 747 Vision) and to adjust bali roadmap
- T/F team will establish the 4<sup>th</sup> total countermeasures of climate change('08~'12) to quantify total GHG reduction target and make sectoral roadmap for Low Carbon Society
- Korea government are discussing the Low Carbon Society scenarios and vision now to reduce GHG emissions
- GHG reduction will be achieved by improvement of technology level and change of social structure in 2050 year

# **LCS Scenarios Summary**

	Scenario A	Scenario B				
GDP (annual)	3.36%	2.98%				
Population('000)	42,343	43,623				
Household('000)	18,330	18,252				
Average family members	2.21	2.39				
Urbanization rate	93%	88%				
Market	- Deregulation	- Adequate rules and regulations				
Life style	- convenient lifestyle	- Reducing the attraction towards apartment complex				

# **Socio-Econ**omic Projections







**Population and household** 



**Industrial structure** 



Year	Scenario A	Scenario B
2000-2004	5.42	5.42
2005	4.20	4.20
2006-2010	4.67	4.07
2011-2020	4.12	3.62
2021-2030	3.48	3.08
2031-2040	2.68	2.38
2041-2050	2.51	2.31
2005~2050 average	3.36	2.98

Source : GDP growth rate is based on the potential GDP growth rate form Korea Energy Economics Institute (KEEI) and internal document of Korea Environment Institute (KEI)

# **Projection** of Population



Scenario A : projection from Korea National Statistical Office's (KNOS) prospect data is used. Scenario B : It is assumed that scenario B will have higher birth rate than scenario A.

### Household and average family members



Scenario A : data from Korea National Statistical Office's (KNSO) is used for 2005~2030 and the projection from 2031 to 2050 is estimated.

Scenario B : Small increase of birth rate compare to that of Scenario A and number of average household members decreases than that of Scenario A.

### **Population** structure by age

- In 2050 korea become ageing society



Scenario A : projection from Korea National Statistical Office's (KNOS) prospect data is used. Scenario B : It is assumed that scenario B will have higher birth rate than scenario A.

### **Industrial structure**

- Increase in GDP share due to growth of IT and finance sector
- Scenario B has a large share of agricultural sector than that of scenario A due to less urbanization
- Service industry will grow up continuously



Data from 2005 to 2030 are from KIET. From 2031 to 2050, the share of each industry is estimated by each scenario

## **Industrial structure**

### **Major premises**

- The major manufacturing industry Information & Communication Technology (ICT), automobile, and ship-building – are expected to lead the economic growth by advancing the industries.
- Agriculture, forestry, and fisheries: higher demands on organic product will raise the value of primary industry (Scenario B).
- Publication and Printing industry: Expansion of computer and informatization tools will reduce the importance of publishing business.
- Education and Research: Transition to knowledge-based society and lifelong education system will further develop education industry.
- Real estate: Decline of number of households and decentralization will reduce the momentum.
- Transportation: Full adoption of five-day workweek and development of entertainment business will increase the potential transportation demand.

# **Modeling Approach**

- Energy snap shot tools is used to calculate energy consumption of end use sector
- To calculate modal share in transportation sector AIM Enduse model is used
- The volume of service on each energy use type is calculated through national projection data and trend analysis based on previous data
- Total amount of electric energy demand is compare with internal MOICE (Ministry of Commerce, Industry, Energy) power generation plan

## **Industrial sector**

### Service volume

- Non-Ferrous, Machinery, and Transport Equipment sector will dominant in secondary industry

Sector	Unit	2005	2050A	2050B
Agriculture and fishery	Billion KRW	39,228	80,145	94,403
Mining and Quarrying	Billion KRW	3,360	4,958	4,204
Food	Billion KRW	68,276	77,427	79,357
Textile and Leather	Billion KRW	44,894	48,505	47,942
Paper, Print, Wood	Billion KRW	45,942	47,297	46,936
Chemical and Petrochemical	Billion KRW	160,336	210,302	203,842
Non-Metallic Minerals	Billion KRW	23,412	24,165	23,949
Iron and Steel	Billion KRW	76,515	88,248	85,330
Non-Ferrous, Machinery, Transport Equipment	Billion KRW	355,719	1,042,513	870,474
Non-specified (Industry)	Billion KRW	40,417	40,775	40,949
Construction	Billion KRW	141,047	166,805	158,207

Numbers from KEEI internal sources for 2005~2030, and the estimation with weight is done for the period of 2031~2050
Share of each sector is estimated using data from KEEI and the estimated share is used on calculating value-added for each sector.

## **Industrial sector**

### **Fuel conversion and efficiency**

#### (1) Fuel conversion

(Scenario A and Scenario B)

- Natural gas will substitute for coal and oil (except for steel, chemical and construction industries.)
- Biomass will be utilized in some industries.

#### (2) Energy efficiency

- In the steel industry, energy efficiency will be improved through development of optimized production method and efficiency enhancement of a furnace.
- Energy efficiency will be upgraded as a result of the introduction of high-efficiency boilers and motors throughout the production process.
- The energy efficiency will reach to the level of Japan.

## **Residential** sector

#### **Basic assumptions**

	2005	2050 A (increasing rate)	2050 B (increasing rate)
Households('000)	15,971	18,330 (14.7)	18,252 (14.3)
Average floor area/ person	20.2	40 (51.4)	36 (47.4)

#### (1) Number of households

- The estimated number of households using the data of 2030 provided by the Korea National Statistical Office is followed
- Scenario B has a greater individual household share than that of Scenario A.

#### (2) Average floor area

- Increased ratio of floor area is calculated through multiplying average per capita floor area by average number of household members.
- The figure in 2050 is estimated based on the data for the average floor area of 2020 which was projected by Korea Research Institute for Human Settlements (KRIHS)

# **Residential sector**

### Service volume and Energy share

- The conservation ratio is equal to CM/REF level backed by diverse policies, energysaving products, insulation, and changes in living patterns

			2050									
	Unit	2005	R	EF	C	М	CM/REF					
			А	В	А	В	А	В				
Space cooling	Mtoe	1.6	5.8	4.2	5.0	3.3	85%	80%				
Hot water and heating	Mtoe	10.1	16.6	13.6	14.9	12.2	90%	90%				
Cooking	Mtoe	1.6	1.9	1.9	1.9	1.9	100%	100%				
Lighting	Mtoe	1.0	1.7	1.4	1.6	1.2	90%	85%				
Refrigerators	Mtoe	0.5	1.0	0.7	1.0	0.7	100%	100%				
ICT appliance	Mtoe	0.7	2.7	1.7	2.5	1.5	95%	90%				
Cloth washers	Mtoe	0.2	0.2	0.2	0.2	0.2	100%	100%				
Other Appliance	Mtoe	1.1	3.8	2.1	3.4	1.8	90%	85%				

- In case of hot water and heating service, oil-boilers will be replaced by others such as solar thermal energy generators, electric-boilers and gas-boilers due to high oil prices.
- Scenario B has more environmentally-friendly energy share than Scenario A.
- In case of cooking, electricity will have a bigger share.

# **Commercial sector**

### **Basic assumptions**

- The increasing rate of 2050 is computed through the analysis of variations of building area, reflecting the basis year data from the National Statistics Office.
- Each energy service demand is calculated after estimating energy share in 2050 reflecting the variations in building floor area and demand for the total energy.

	2005	2050 A	2050 B
Hot water and heating	100	151.35	133.84
Cooling	100	158.16	139.27
Cooking	100	130.65	117.34
Other Appliance	100	153.23	135.34
Motor etc.	100	152.65	134.87
Lighting	100	150.19	132.91

Energy consumption per floor area for energy service (100 in 2005)

### **Commercial sector**

#### Service volume and Energy share

			2050									
	Unit	2005	RI	EF	C	М	CM/REF					
			А	В	А	В	А	В				
hot water and heating	Mtoe	4.5	11.0	8.8	8.8	7.0	80%	80%				
Space cooling	Mtoe	2.2	5.8	4.6	5.0	3.9	85%	85%				
cooking	Mtoe	1.2	2.2	1.7	2.2	1.7	100%	100%				
Facilities	Mtoe	3.0	7.5	5.9	6.7	5.4	90%	90%				
Self-Generation	Mtoe	0.0	0.1	0.1	0.1	0.1	100%	100%				
Lighting	Mtoe	1.7	4.2	3.4	3.8	3.0	80%	90%				

- Energy demand will be reduced in the CM case through waging energy conservation campaigns, popularizing energy saving buildings, enforcing insulation of buildings, recommending changes in life patterns and utilizing automatic temperature control devices.

	OIL	GAS	BMS	S/W	Heat	ELE	OIL	GAS	BMS	S/W	Heat	ELE
hot water and heating	5	30	-	5	15	45	10	15	10	20	-	45
Space cooling	-	-	-	_	-	100	-	-	-	-	-	100
cooking	-	65	-	-	-	35	-	50	20	-	-	30
Facilities	-	-	-	-	-	100	-	-	-	-	-	100
Self-Generation	20	80	-	-	-	-	20	80	-	-	-	-
Lighting	-	-	-	-	-	100	-	-	-	-	-	100

# **Passenger** transportation Sector

### Service volume

- Scenario B reflects a reduction of 10% in the total passenger demand compared to Scenario A, taking into consideration the bike-related policy announced by Ministry of Government Administration and Home Affairs



Domestic demand alone is taken into account in estimating demand for shipping by air or sea

## **Passenger** transportation Sector

### Service share and Energy efficiency

			205	0 A		2050 B						
	OIL	GAS	BMS	S/W	H2	ELE	OIL	GAS	BMS	S/W	H2	ELE
Mini prv.	10	20	-	-	40	30	20	20	30	-	-	30
Small Prv.	30	20	20	-	30	-	10	20	40	-	-	30
Large Prv.	40	30	-	-	30	-	40	20	40	-	-	-
Commercial pss.	30	20	-	-	50	-	50	-	50	-	-	-
Bus	20	20	20	-	40	-	10	40	50	-	-	-
Train	-	-	-	-	-	100	-	-	-	-	-	100
Ship	50	-	50	-	-	-	50	-	50	-	-	-
Air	100	-	-	-	-	-	100	-		-	-	-

- The average fuel efficiency of the internal-combustion engines of cars will be triple that of 2005 and the average COP of internal-combustion engines powered by hydrogen fuel cells and electricity will be boosted from 3.0 to 4.0 and from 3.0 to 5.0 respectively.

- The fuel efficiency of trains will be double that of 2005.
- The fuel efficiency of ships will be 1.33 times higher than that of 2005.
- Airplanes will have a 1.5 times higher energy efficiency than that of 2005 on average

# **Freight transportation sector**

#### Service volume

(Unit : mil-ton Km)



Domestic demand alone is taken into account in estimating demand for shipping by air or sea

## **Freight transportation sector**

### Service share and Energy efficiency

		2050 A								2050 B					
	OIL	GAS	BMS	S/W	Heat	H2	ELE	OIL	GAS	BMS	S/W	Heat	H2	ELE	
Freight (<1ton)	15	15	-	-	_	45	25	-	-	50	-	-	-	50	
Freight (>1ton)	60	5	-	-	-	35	-	-	-	-	-	-	-	100	
Train	-	-	-	-	-	_	100	_	_	_	-	-	-	100	
Ship	100	-	-	-	-	-	-	50	-	50	-	-	-	-	
Air	100	-	-	-	-	-	-	100	-	-	-	-	-	-	

- The average fuel efficiency of the internal-combustion engines of small freight cars will be three times higher than it was in 2005 while the average COP of internal-combustion engines operated by hydrogen fuel cell and electricity will increase from 3.0 to 4.0 and from 3.0 to 5.0 respectively.
- The average fuel efficiency of the internal-combustion engines of mid-sized freight cars will be 1.52 times higher than it was in 2005 while the average COP of internal-combustion engines operated by electricity will rise five times between 2005 and 2050.
- The fuel efficiency of trains will be double that of 2005.
- The fuel efficiency of ships will increase by 1.33 times between 2005 and 2050.
- The average fuel efficiency of airplanes will improve by 1.5 times during the same period.

# **Power generation sector**

#### **Energy mix**



- Each scenario estimates the amount of power generated by each energy source in 2050 based on the Power Sector Plan (2005 – 2020) of MOCIE(Ministry of Commerce, Industry and Energy)
- Midnight electric power or wind power is utilized to meet demand for hydrogen-based energy in the transportation sector
- The CO<sub>2</sub> emitted from coal and gas thermal power generation and the CO<sub>2</sub> emitted during natural gas reforming for the purpose of hydrogen production is subjected to carbon capture and storage



### Result

# **Industrial sector**





 $\mathrm{CO}_2$  emission in industrial sector with allocated emission from heat, H2, electricity (MtC)



• Total CO<sub>2</sub> emission reduction

- Scenario A : 2% from base year
- Scenario B : 14% from base year

Energy consumption in industrial sector (Mtoe)

# **Residential** sector





 $\mathrm{CO}_2$  emission in residential sector with allocated emission from heat, H2, electricity (MtC)



#### Total CO<sub>2</sub> emission reduction

- Scenario A : 21% from base year
- Scenario B : 48% from base year

Energy consumption in residential sector (Mtoe)

# **Commercial sector**





 $CO_2$  emission in commercial sector with allocated emission from heat, H2, electricity (MtC)



#### Total CO<sub>2</sub> emission reduction

- Scenario A : 18% from base year
- Scenario B : 48% from base year

Energy consumption in commercial sector (Mtoe)

## **Transportation sector**



- Total CO<sub>2</sub> emission reduction
- Scenario A : 75% from base year
- Scenario B : 79% from base year

- Scenario A : 27% from base year
- Scenario B : 70% from base year



#### Factor analysis

				205	50 A		2050 B						
		IND	RES	СОМ	TR-P	TR-F	Total	IND	RES	СОМ	TR-P	TR-F	Total
Change rate	D	38%	51%	69%	5%	46%	43%	31%	24%	42%	-5%	15%	26%
2050/2005	E/D	-12%	-42%	-37%	-54%	-60%	-31%	-13%	-36%	-32%	-48%	-50%	-28%
	C'/E	-9%	-6%	-19%	-29%	-14%	-13%	-11%	-13%	-25%	-18%	-15%	-15%
	C/C'	-19%	-24%	-31%	2%	1%	-17%	-20%	-23%	-32%	-8%	-19%	-21%
	Total	-2%	-21%	-18%	-75%	-27%	-17%	-14%	-48%	-48%	-79%	-70%	-38%
CO2 share	2005	46%	14%	17%	9%	14%	100%	46%	14%	17%	9%	14%	100%

- The CO<sub>2</sub> emissions in 2050 will be reduced by 17% in Scenario A, and 38% in Scenario B respectively as compared to 2005.
- It is worthwhile to note that approximately 8% of CO<sub>2</sub> emissions will captured by CCS.





■ 2050 A ■ 2050 B

# **Policy Issues**

- Extend the use of low carbon energy
- Increase investment of renewable energy (solar, wind, etc)
- Introduce a partial reduction duty using Renewable Portfolio Agreement (RPA)
- In industrial sector, strengthen of voluntary agreement (Voluntary Agreement → Negotiated Agreement)
- Advancing a whole nation energy frugality campaign with citizen group

# **Conclusion and remarks**

- 17~38% CO<sub>2</sub> reduction will be achieved than that of 2005 when improvement of technology, change of energy mix and reduction of CO<sub>2</sub> emission using CCS are realized
- It is difficult to setting up the CO<sub>2</sub> emission reduction target than that of 1990 because of korea socio-economic states (3.8% GDP annul growth, Increasing population and household)
- Current korea's technological level related CO<sub>2</sub> reduction is
   60~75% than that of advanced country. Intensive investment in te chnology is needed to achieve Low Carbon Society
- If next government should give priority to economy to achieve 7% growth rate of GDP, more policy alternative should be needed to reduce CO<sub>2</sub> emissions

# **Conclusion and remarks(2)**

- In power generation sector, the amount of generated nuclear power will increase based on the MOCIE 2020 plan. But social agreement is necessary to construct more new nuclear power generator
- In transportation sector, korea government plan to intensive investment to construct hydrogen station to change automobile standard with 4 stage construction plan
- To reduce CO<sub>2</sub> emissions in industrial sector, korea have to change its structure from steel and petro-industry to design, R&D and knowledge based industry



- Data Supplement to match up new economical policy and adjust bottom up approach
- Design of policy roadmaps toward the Low Carbon Society
- Feasibility analysis of the roadmaps considering the policy
- Application of ESS model to local area to check up possibility